

safetymax® L325



NEW SAFETymax DISTRIBUTION BOARDS WITH W325mm

Insulation Class II with aluminum frame and door	Rows x Modules: 2x12; 3x12; 5x12	Depths: 90 and 125mm
Flush and Surface mounted applications	Removable chasis	IP54 and IK07

FLUSH MOUNTED APPLICATION (FM)

CODE	DESIGNATION	DIMENSIONS (WxHxD)
+32816	DISTRIBUTION ENCL (2x12) 24md D90 FM	325x375x90
+32820	DISTRIBUTION ENCL (2x12+1x11) 35md D90 FM	325x500x90
+334	DISTRIBUTION ENCL (2x12) 24md D125 FM	325x375x125
+337	DISTRIBUTION ENCL (3x12) 36md D125 FM	325x500x125
+34906	DISTRIBUTION ENCL (5x12) 60md D125 FM	325x750x125

SURFACE MOUNTED APPLICATION (SM)

CODE	DESIGNATION	DIMENSIONS (WxHxD)
+32866	DISTRIBUTION ENCL (2x12) 24md D90 SM	325x375x90
+32870	DISTRIBUTION ENCL (2x12+1x11) 35md D90 SM	325x500x90
+357	DISTRIBUTION ENCL (2x12) 24md D125 SM	325x375x125
+360	DISTRIBUTION ENCL (3x12) 36md D125 SM	325x500x125
+37206	DISTRIBUTION ENCL (5x12) 60md D125 SM	325x750x125