

## DATASHEET

+37238



### DISTRIBUTION ENCL (6x24) 144md D125 SM

Dimensions WxHxD (mm)	550x875x125
EAN	5600307030936
Rows x Modules	6x24
Application	Surface Mounted (SM)
No. Frames for DIN rail	6
Locking System	2 Flat plastic handle lock
Color	White - RAL 9010
Tariff Code	85381000
Gross Weight (Kg)	15
Volume (m <sup>3</sup> )	0.083

### Materials

Enclosure	Plastic - PSHI
Frame and door	White lacquered aluminium
Chassis	Aluminium
BUSBARS	PA support and brass busbar

### Protection and Security

Insulation Class	Class II Insulation
IP Protection Degree	54
IK Protection Degree	09
GWT	850°C
Static Load	200kg/m <sup>3</sup>
Mechanical Reinforcement	Sim
Installation Temperature	Mín: -5°C Máx: 40°C

### Electrical Features

In	125A
Ue	230V/400V~
Ui	690V
Pde - 30K	92,5W
Frequency	50Hz

### Included Accessories

Neutral Nº Busbars	5x(1x25mm <sup>2</sup> + 9x16mm <sup>2</sup> ) 2x(12x10mm <sup>2</sup> + 11x16mm <sup>2</sup> )
Earth Nº Busbars	4x(1x25mm <sup>2</sup> + 9x16mm <sup>2</sup> ) 2x(12x10mm <sup>2</sup> + 11x16mm <sup>2</sup> )
Blanking Plates	3x12md
Circuit Marking Labels	Yes
Fixing Kit	Sim

## Standardizing Documentation

<b>Standards</b>	EN 62208
<b>Directive</b>	2014/35/UE
<b>Regulations</b>	RTIEBT

**Nota:**The image may not correspond to the product code shown. Please refer to the technical specifications.