

DATASHEET

+60118

DISTRIBUTION ENCL (1x18) 18md IP65 SM



Dimensions WxHxD (mm)	428x258x144
EAN	5600307039946
Rows x Modules	1x18
Application	Surface Mounted (SM)
No. Frames for DIN rail	1
Locking System	Flat plastic handle lock
Color	Grey - RAL 7035
Tariff Code	85381000
Gross Weight (Kg)	2.15
Volume (m³)	0.01729

Materials

Enclosure	Plastic - ASA
Frame and door	Polycarbonate transparent door
Chassis	Aluminium
BUSBARS	ABS, Polycarbonate and fiberglass

Protection and Security

Insulation Class	Class II Insulation
IP Protection Degree	65
IK Protection Degree	08
GWT	650°C
Installation Temperature	Mín: -5°C Máx: 40°C

Electrical Features

In	63A
Ue	400V
Ui	500V
Pde - 30K	20W
Frequency	50Hz

Included Accessories

Neutral Nº Busbars	1x(15x16mm2)
Earth Nº Busbars	1x(15x16mm2)
Blanking Plates	0,5x12md
Circuit Marking Labels	Yes
Fixing Kit	Sim

Standardizing Documentation

Standards	EN 62208
Directive	2014/35/UE
Regulations	RTIEBT

Nota:The image may not correspond to the product code shown. Please refer to the technical specifications.